

LIMITATIONS/PROVISIONS ON THE USE OF A REGIONAL HAULING PERMIT

ACCEPTANCE OF RESPONSIBILITY / INSURANCE COVERAGE

1. Permittee agrees to pay the cost of repairing any and all damages caused to the highways or structures by reason of the above mentioned hauling and agrees to hold the Permitting Authority/Local Authority harmless from all liability.
2. Any vehicle being operated under the authority of a permit must have current automobile insurance and be covered by a minimum of \$500,000.00 Property Damage Liability Insurance. All stipulations of ODOT's OS-32 form shall be applicable.

GENERAL LIMITATIONS

1. A copy of the valid Regional Heavy Haul Permit (RHHP) as issued shall be in the possession of the driver at all times during the progress of transportation and shall be shown on demand to any law enforcement officer, employee of the Ohio State Highway Patrol or to any employee of the office of the Permitting Authority. The driver is responsible to identify and present the precise copy of the RHHP covering the movement of the vehicle/load being moved. The RHHP shall be clearly legible, free of any markings, writing, symbol, logo, letterhead, characters or inscriptions that are not part of the RHHP as approved by the Local Authority (an additional tele-facsimile header is allowed).
2. The permission granted restricts the movement of the vehicle(s) or object(s) to the roadways specified, between points designated, and within the time allotted. Permittee is responsible to check the route for abnormal, changed, or unknown/unusual conditions which may exist during any move. Permittee is responsible to ensure safe movement over or across any railroad crossing. **Permission to travel on any roadway not specified on this permit must be obtained from the authority with jurisdiction over that roadway.**
3. No vehicle(s) or object(s) being moved under the authority of a RHHP shall be left parked on the roadway either day or night except in the case of an emergency, in which case adequate protection shall be provided for the traveling public. Vehicles shall not be loaded or unloaded within the limits of the roadway unless prior approval has been granted by this office.
4. The operator of the vehicle must comply with all laws, rules, regulations or credentials covering:
 1. The movement of traffic over roadways.
 2. Commercial Motor Vehicle operations (I.R.P., C.D.L., I.F.T.A., U.C.R., Load Securement, etc.)
5. Any vehicle/load being moved under the authority of a RHHP must be adequately described.
6. A RHHP is void at any time road, weather or traffic conditions make travel unsafe, as determined by local law enforcement or the Ohio State Highway Patrol.
7. Movement of mobile homes, manufactured structures, office trailers, and park model recreational vehicles is prohibited when wind velocity exceeds 25 mph on the roadway or 15 mph on bridges.

OPERATING LIMITATIONS

1. No vehicle(s) or object(s) being transported under a RHHP shall travel in a convoy with any other oversize/overweight vehicle or vehicle and load. Convoying is defined as operating within 500' of any other permitted vehicle that is traveling in front of and in the same direction as said vehicle.
2. Any vehicle or load with an overall height in excess of 13'6" shall be required to coordinate the move with the owners of all overhead signs, signals, utilities, etc., which may obstruct safe, clear movement.
3. Reductions in legal weight posted on roadways or bridges must be obeyed unless specifically authorized in the RHHP.

DAYS/HOURS OF OPERATION

1. Overweight vehicles/loads that are not over dimensional, traveling under the authority of a RHHP, will not be restricted as to travel hours or days so long as the overweight vehicle/load can move without obstructing the normal flow of traffic.
2. With the exception of permitted legal dimensioned overweight vehicle/loads noted in 1. above, vehicle/loads traveling under the authority of a RHHP shall be prohibited from movement on the following days/weekends: **New Year's Day, Memorial Day, Independence Day, Labor Day, Thanksgiving Day and Christmas Day.** Prohibitions begin at noon the day preceding and continue until one-half hour before sunrise the day following the holiday or holiday weekend.
3. Movement of all vehicles/loads in excess of twelve feet in width shall be prohibited during the following travel times:
 - Saturday from 3 P.M. until one-half hour before sunrise the following Sunday.
 - Sunday from 3 P.M. until one-half hour before sunrise the following Monday.
 - Friday from 3 P.M. until one-half hour before sunrise on the following Saturday (April 1 through November 30).These time limitations are in addition to those listed in item #2 of the **Days/Hours of Operation.**
4. With the exception of limits noted in 1, 2 & 3 above, permitted vehicles/loads may move daylight hours, Sunday through Saturday. Daylight hours are defined as one-half hour before sunrise to one-half hour after sunset.

WARNING FLAGS AND SIGNS

1. Warning flags shall be displayed on all over dimensional vehicles and loads. Warning flags shall be 18 inches square, red or orange in color, in good repair and free of printing or other markings and shall be securely fastened by at least one corner or securely mounted on a staff.
2. Over width vehicles and loads shall bear two flags at the widest extremities of the vehicle or load. Warning flags are not required to be displayed on the tractor.

CONTINUED ON PAGE 2

3. Over length vehicles and loads or vehicles and loads with a rear overhang of 4 feet or greater shall display a single flag at the extreme rear if the over length or projecting part is two feet wide or less. Two flags shall be displayed if the over length or projecting portion is wider than two feet and the flags should be located to indicate maximum width.
4. Warning signs, when required, shall be in good repair, shall read “**OVERSIZE LOAD**” and shall be at least 7 feet long and 18 inches high. The sign’s background shall be yellow with black lettering. Letters shall be at least 10 high with a 1.41 inch brush stroke. If series E Modified is used, the brush stroke is to be two inches.
5. **OVERSIZE LOAD** signs shall be displayed on any vehicle or vehicle/load:
 - exceeding the maximum legal length limit as set in the Ohio Revised Code, section 5577.05,
 - with an overall width of **10 feet or greater**,
 - with an overall height in excess of **14 feet 6 inches**.
 When required, **OVERSIZE LOAD** signs, shall be displayed on the front and rear of the over dimensioned vehicle or vehicle/load.

LIGHTING

1. All permitted vehicle’s standard vehicle lighting must be in operating order; **THE HEADLIGHTS MUST BE ON DURING THE MOVEMENT OF ANY OVER DIMENSION VEHICLE/LOAD.**
2. **PERMITTED VEHICLE SPECIAL LIGHTING** - Clearance and side marker lights, in addition to the standard lights required by law, need not mark the extremities or an oversize load unless it is specially authorized to move at night or when visibility is less than 1,000 feet, in which case, the additional lighting shall be displayed in the manner described in the Ohio Department Of Transportation’s **OPERATIONAL REQUIREMENTS** section of the Special Hauling Permits **OPERATIONAL GUIDE**.

PRIVATE ESCORT VEHICLES

1. Private Escort vehicles, when required by a **RHHP** to accompany an over dimensional or overweight vehicle or vehicle/load, shall be required to display a warning sign, yellow with black letters, reading “**OVERSIZE LOAD**”. The sign shall be 5 feet long by 12 inches high with 8 inch high letters and shall be in good repair. Escort vehicles shall also be required to maintain radio communication with the operator of the permitted vehicle and shall also be required to be equipped with a roof mounted amber flashing or rotating light(s). Driver of the escort vehicle is to act as a flagger when needed. The Driver of an escort vehicle shall not serve as an operator of other vehicles or equipment while escorting a vehicle/load operating under a RHHP. Unless otherwise specified on the RHHP, Public Safety/Law Enforcement Vehicles shall not be considered to be Private Escorts.
2. **One Rear** escort vehicle shall be required for the transportation of any vehicle/load with a permitted length in excess of 90 feet.
3. **One Lead** (rear on multiple lane highways) escort vehicle shall be required for the transportation of any vehicle/load with a **permitted width in excess of 13 feet**.
4. **One Lead** escort vehicle equipped with a height sensing device shall be required for the transportation of any vehicle/load with a permitted height in excess of 13 feet 6 inches.
5. **One Lead and One Rear** escort shall be required on any vehicle/load with a **permitted width in excess of 14 feet 6 inches**, or on any vehicle/load with a **permitted height in excess of 14 feet 10 inches**.
6. If more than one of the conditions set forth in numbers 2 through 4 above are met, (for example, a load with a permitted width exceeding 13 feet and a permitted length exceeding 90 feet) **two escorts** (one lead and one rear) shall be required.
7. Front and rear escort vehicles, when required, shall maintain a safe operating distance consistent with existing traffic conditions between the vehicle/load being escorted and the escort vehicle.
8. Escort vehicles shall be a single unit vehicle with unobstructed vision from the front and rear. Escort vehicles, when accompanying a vehicle/load operating under a RHHP shall not tow a trailer or another vehicle, or haul equipment which extends beyond the dimensions of the escort vehicle.

PENALTIES FOR VIOLATION

1. Failure to comply with the RHHP provisions or the general provisions contained herein, or exceeding the gross vehicle weight or exceeding an axle or axle group weight (by more than 2,000 pounds) or exceeding the dimensions granted, or operating on dates or at times, or upon roadways other than assigned, or whenever the RHHP does not adequately describe the vehicle/load, **shall render the RHHP null and void and the operator of the vehicle will be subject to enforcement action**, as provided in sections 5577.02 to 5577.05 inclusive, of the Ohio Revised Code.
2. A **RHHP** should not be voided when a vehicle exceeds a granted axle weight by 2,000 pounds or less, provided that the vehicle does not exceed the gross vehicle weight granted by the **RHHP**. The enforcing officer shall instruct the driver to bring the vehicle into compliance with the **RHHP** prior to substantial movement. If the load cannot be brought into compliance, the load may not move until a revised **RHHP** is obtained. Should the vehicle be moved prior to the vehicle being brought into compliance or prior to a revised **RHHP** being obtained, the **RHHP shall be rendered null and void and the operator will be subject to enforcement action** as provided in sections 5577.02 to 5577.05 inclusive, of the Ohio Revised Code.
3. Moving violations for offenses that are relevant to the safe movement of a Commercial Motor Vehicle (for example, Speed, Reckless Operation, DUI, Improper Lane Change, etc.) **shall render the RHHP null and void, and the operator subject to additional enforcement action**.

These limitations and provisions describe the general requirements placed on the operation of over dimension and overweight vehicles traveling on Ohio’s roadways, and are in addition to specific provisions stated on the RHHP or its attachments. For answers to any questions regarding the proper or allowable movement of a vehicle/load covered by a RHHP, contact the permitting authority listed on the permit prior to any movement. Any authorization granted by the issuance of a RHHP is revoked at any time a permitted vehicle/load is engaged in Unpermitted Movement.